

# TASKalfa 6002i

BLACK & WHITE MULTIFUNCTIONAL SYSTEM

# POWERFUL PERFORMANCE... CONNECTING INFORMATION AND WORKFLOW.



The TASKalfa 6002i is a best-in-class Black and White MFP that combines print, copy, and color scan functionality into one powerful platform. To ensure that your organization runs at peak efficiency, the TASKalfa 6002i offers an unmatched array of standard features, professional finishing options, and host of customizable business applications that further streamline workflow. Add to that Kyocera's award-winning ultra-reliability and unique long-life technology, and proven leadership in technology innovation, and the TASKalfa 6002i will transform end-to-end document processes...and drive bottomline business growth.

- > Crisp Black and White Output up to 60 Pages per Minute
- > Exceptional Print Quality at up to 1200 dpi
- > Scalable Paper Capacity for Longer Job Runs

- > Flexible Media Support and Paper Sizes up to 12" x 48"
- Customizable 9" Color Touch Screen with Intuitive, Tablet-like Home Screen
- > Robust Portfolio of Business Applications for Enhanced Capabilities, such as Scan Distribution to Back-end Applications and Document Management Systems
- > Advanced Finishing Options for Professional Output, including a 4,000-sheet External Finisher and optional Booklet Folding
- > Standard USB Host Interface for On-the-Go Printing and Scanning
- > Efficient Color Scanning up to 180 ipm
- > Convenient Wireless Printing and Scanning
- > Apple AirPrint<sup>®</sup>, Google Cloud Print<sup>™</sup> and KYOCERA Mobile Print Compatible for a Mobile Printing Solution



# TASKalfa 6002i

# BASIC SPECIFICATIONS

Configuration: Black & White Multifunctional System – Print/Scan/Copy/Optional Fax Pages Per Minute: Letter: 60 ppm, Legal: 36 ppm, Ledger: 30 ppm,

12" x 18": 30 ppm (print only) Warm Up Time: 17 Seconds or Less (Power On)

First Page Out:

Copy: 3.4 Seconds or Less Print: 3.8 Seconds or Less

Display: 9" Color Touch Screen Control Panel

Resolution / Bit Depth: 600 x 600 dpi; 9600 dpi x 600 dpi; 1200 x 1200 dpi

Memory / Hard Disk Drive: 4GB RAM / 8GB SSD / 320GB HDD Standard

**Duplex:** Standard Stackless Duplex Supports Statement to 12" x 18", 14 lb Bond – 166 lb Index (52 – 300gsm)

Standard Output Tray: Statement - 12" x 18" / 500 sheets; up to 12" x 48" Banner (Single Sheet)

Electrical Requirements: 120V, 60Hz, 12A; 220-240V, 50Hz, 7.2A Typical Electricity Consumption (TEC): 120V: 3.0 kWh/week; 220V: 3.0 kWh/week

Dimensions: 23.70" W x 26.18" D x 31.10" H

Weight: 180.78 lbs

Maximum Monthly Duty Cycle: 250,000 Pages per Month PAPER SUPPLY

Standard Paper Sources: Dual 500 Sheet Trays, 150 Sheet MPT, Auto Selection/Switching

Optional Paper Sources: Dual 500 Sheet Trays (PF-7100), Dual 1,500 Sheet Trays (PF-7110); Side LCT: 3,000 Sheet Capacity Tray (PF-7120)<sup>1</sup>

Paper Capacity: Standard: 1,150 Sheets; Maximum: 7,150 Sheets Paper Size:

Tray 1 – 5.5" x 8.5" – 8.5" x 14" (Statement to Legal); Tray 2 – 5.5" x 8.5" – 12" x 18", Custom Size; **PF-7100**: 5.5" x 8.5" – 12" x 18"; **PF-7110**, **PF-7120**: 8.5" x 11"; **MPT**: 5.5" x 8.5" – 12" x 18" (Multiple Sheets); Up to 12" x 48" Banner (Single Sheet)

Paper Weight: Trays / MPT: 14 lb Bond – 166 lb Index (52 – 300gsm)

Input Materials: Standard/Optional Drawer: Plain Paper, Bond Paper, Recycled Paper, Envelopes; MPT: Plain Paper, Bond Paper, Recycled Paper, Cardstock, Transparencies, Labels, Envelopes

# SECURITY SPECIFICATIONS

Standard: Local Authentication, Network Authentication (IPsec, HTTPS, LDAP over SSL, SNMPv3); Secure Print (IPP over SSL); Scan to Email (POP3/SMTP over SSL); Scan to FTP (FTP over SSL); Scan to SMB/PC/USB; FTP over SSL

**Optional:** Data Security Kit (E): HDD Overwrite Mode, HDD Data Encryption

# PRINT SPECIFICATION

Standard Controller: Freescale QorlQ T1024 (Dual Core) / 1.2GHz PDLs / Emulations: PRESCRIBE, PCL6 (PCL-XL / PCL5), KPDL3 (PS3), XPS, OPEN XPS; Optional (UG-34): IBM ProPrinter, Line Printer, LQ-850

Print Resolution: Up to 1200 x 1200 dpi

Fonts: 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap OS Compatibility: Windows: XP/Vista/7/8/8.1/10/Server 2003/ Server 2008/Server 2008 R2/Server 2012/Server 2012 R2; Novell NetWare 3.x/4.x/5.x/6.x; Mac OS 10.x; AirPrint Enabled; Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)

Mobile Printing: Apple AirPrint®, Google Cloud Print™, KYOCERA Mobile Print Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host Interfaces, 2 Expansion Slots

Optional: 10/100/1000BaseTX (**IB-50** for Dual NIC), IEEE 802.11 b/g/n (**IB-51** for Wireless LAN Interface)

Network Print and Supported Protocols: TCP/IP, NetBEUI, IPv4, IPv6, IPsec, HTTP, LPD, FTP, IPP, RawPort, LLTD, SNTP, DHCP, SMTP, POP3, DNS, SNMPv1/v2, WSD Scan/Print

Drivers: KX Driver, PCL Mini Driver, KPDL Mini Driver, KX Driver for XPS, Network Fax Driver, TWAIN Driver, WIA Driver, PPD for MAC, PPD for Linux

Utilities: KYOCERA Net Admin, KYOCERA Net Viewer, PDF Direct Print, Command Center RX

# SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi

File Formats: TIFF (MMR compression), PDF (MMR compression), PDF (high compression), OpenXPS, XPS, JPEG

#### PDF Extension: Searchable PDF (OCR) Option Scan Speeds (mono/color, @300 dpi):

DP-7100: Simplex: 80 ipm B&W / 80 ipm Color; Duplex: 48 ipm B&W / 48 ipm Color

**DP-7110:** Simplex: 100 ipm B&W / 100 ipm Color; Duplex: 180 ipm B&W / 180 ipm Color

Connectivity / Supported Protocols: 10/100/1000BaseTX, TCP/IP,

Hi-Speed USB 2.0

Scanning Functions: Scan to Folder (SMB), Scan to Email, Scan to FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan Original Size: Through DP: Statement to Ledger (5.5" x 8.5" – 11" x 17"); Glass: Up to 11" x 17"

Drivers: TWAIN/WIA Driver

# COPY SPECIFICATIONS

Copy Resolution: 600 x 600 dpi Image Mode: Text, Photo, Text/Photo, Graphic/Map

Continuous Copy: 1 – 999 / Auto Reset to 1 Additional Features: Auto Magnification, Auto Paper Select, Auto Start, Auto Drawer Change, Interrupt Copy, Positive / Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed Through, Text Stamp, Bates Stamp, Blank Page Skip

Job Management: 1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy

**Color Adjustment:** One Touch, Hue, Auto Exposure, Sharpness **Magnification / Zoom:** Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 – 400% in 1% Step Increments

Document Box: Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

#### OPTIONAL DOCUMENT PROCESSORS<sup>2</sup> Type / Capacity:

DP-7100: Reversing Automatic Document Processor / 140 Sheets DP-7110: Dual Scan Document Processor / 270 Sheets Acceptable Originals: 5.5" x 8.5" - 11" x 17"

## Acceptable Weights:

DP-7100: Simplex: 13 lb Bond – 90 lb Index (45 – 160gsm); Duplex: 16 lb – 32 lb Bond (50 – 120gsm) DP-7110: Simplex: 13 lb Bond – 120 lb Index (35 – 220gsm); Duplex: 16 lb – 120 lb Index (50 – 220gsm)

OPTIONAL FAX SPECIFICATIONS

# Fax Type: Fax System 12

Compatibility / Data Compression: G3 Fax / MMR, MR, MH, JBIG Transmission Speed / Modem Speed: Less than 3 seconds / 33.6 Kbps Fax Memory: Standard 170 MB Driver: Network Fax Driver Fax Functions: Network Fax, Broadcast, Duplex Transmission/

**Fax Functions:** Network Fax, Broadcast, Duplex Transmission/ Reception, Encrypted Transmission/Reception, Polling Transmission/Reception

# **OUTPUT & FINISHING OPTIONS**

OPTIONAL 500 SHEET INTERNAL FINISHER DF-7100<sup>3</sup> Stack / Staple Capacity: 500 Sheets / 50 Sheets

(up to 24 lb Bond [90gsm]) Paper Size: 5.5" x 8.5" - 12" x 18"

Paper Weight: 14 lb Bond – 166 lb Index (52 – 300gsm) Edge Staple Position: 3 Positions: Front 1 Staple, Edge 1 Staple, Face 2 Staples

Optional Punch: PH-7100 2 and 3 Hole Punch Unit, Supports 5.5" x 8.5" – 12" x 18"; 14 lb Bond – 166 lb Index (52 – 300gsm) Dimensions: 19.60" W x 20.98" D x 6.73" H

### OPTIONAL 1,000 SHEET FINISHER DF-7120<sup>3,4</sup>

Stack / Staple Capacity: Main Tray: 1,000 Sheets / 50 Sheets

(up to 24 lb Bond [90gsm])

Paper Size: 5.5" x 8.5" – 12" x 18"

Paper Weight: 14 lb Bond – 166 lb Index (52 – 300gsm) Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

**Optional Punch: PH-7A** 2 and 3 Hole Punch Unit, Supports 5.5" x 8.5" – 12" x 18"; 14 lb Bond – 166 lb Index (52 – 300gsm) **Dimensions:** 21.57" W x 24.35" D x 41.34" H

# OPTIONAL 4,000 SHEET FINISHER DF-7110<sup>3,4</sup>

Stack / Staple Capacity: Main Tray (A): 4,000 Sheets; Sub Tray (B): 200 Sheets / 65 Sheets (up to 24 lb Bond [90gsm]) Paper Size: 5.5" x 8.5" - 12" x 18"

Paper Weight: 14 lb Bond – 166 lb Index (52 – 300gsm) Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 5.5" x 8.5" – 12" x 18"; 14 lb Bond –166 lb Index (52 – 300gsm) Dimensions: 23.91" W x 26.32" D x 41.78" H

Optional Booklet Folder / Tri-fold Unit<sup>5</sup>: BF-730 Booklet Folder supports 8.5" x 11", 8.5" x 14", 11" x 17"; Fold booklet staple: 16 lb – 24 lb Bond (60 – 90gsm) 16 sheets, 25 lb – 28 lb Bond (91 – 105gsm) 13 sheets; Fold booklet no staple: 16 lb – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120esm) 3 sheets; 32 lb Bond – 110 lb Cover (121 – 256gsm

(91 – 120gsm) 3 sheets; 32 lb Bond – 110 lb Cover (121 – 256gsm) 1 sheet; Trifold supports 8.5" x 11" only: 16 lb – 24 lb Bond (60 – 90gsm) 5 sheets; 25 lb Bond – 72 lb Index (91 – 120gsm) 3 sheets; 16 lb – 28 lb Bond (60 – 105gsm) 1 sheet

**Optional Multi-Bin Mailbox<sup>5</sup>: MT-730(B)** includes 7 Trays; Supports 16 lb Bond – 90 lb Index (60 – 163gsm); Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"

# ADDITIONAL OPTIONS

Bridge Unit Attachment Kit (AK-7100), Banner Guide 10, Internet Fax Kit (A), Card Authentication Kit (B), Gigabit NIC (IB-50), Wireless LAN IEEE802.11b/g/n (IB-51), ThinPrint (UG-33), Emulation (UG-34), Document Tray (DT-7100), Scan Extension Kit (A) for Searchable PDF/OCR, Keyboard Holder 10, Data Security Kit (E), Numeric Keypad (NK-7110), Job Separator (JS-7100)

Requires PF-7100 or PF-7110
Only 1 Document Processor can be installed
Only 1 Output Option can be installed
Requires Bridge Unit Attachment Kit (AK-7100)
Requires DF-7110

**ONLY FROM KYOCERA** 

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, enhanced workflow applications, ease-of-use and durability. Looking to streamline your document workflow? KYOCERA offers a robust portfolio of Business Applications that seamlessly and securely integrate with our MFPs. To learn more about which Business Applications are right for your business, visit the Solutions section on our website.

Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceradocumentsolutions.com/us MAC and AirPrint are trademarks of Apple, Inc. Google Cloud Print is a trademark of Google, Inc. TASKalfa, PRESCRIBE, KX Driver, and Command Center RX are the trademarks of The Kyocera Companies. All other trademarks are the property of their respective owners.

KYOCERA Document Solutions America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA ©2016 KYOCERA Document Solutions America, Inc. IC# 855D400453

