

bizhub 651i

Black & White A3 multifunctional







CUSTOMER BENEFITS



Security

Secure network integration, data encryption, overwrite all data function, and advanced user authentication



Productivity

Reliability, high-speed scanning and printing, combined with powerful finishing functions



Sustainability

Numerous eco features reduce energy consumption and costs



Intuitive operability

Operate the bizhub like a smartphone or tablet with fully customized user interface



Application ecosystem Enhanced efficiency thanks

to Konica Minolta's extensive applications portfolio



Services

Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup

OPTIONS



Unicode fonts


OCR A and B fonts

Document converter pack LK-110v2

ThinPrint® client LK-111

Antivirus







Working table

10-Key pad Security kit

Replacement SSD

Keyboard holder KH-102

MEDIA INPUT

Intelligent media sensor IM-103

1x Universal tray PC-116

2x Universal tray

Large capacity tray PC-417

Large capacity tray

Large capacity tray LU-207

Banner tray

MEDIA OUTPUT

Output tray OT-513

Off-line stapler FS-P04

Staple finisher FS-539

unch kit for FS-539/SD

Staple finisher FS-540

Booklet finisher FS-540SD

Punch kit for FS-540/SD PK-526

OR)

Post inserter for FS-540/SD PI-507

Job separator for FS-540/SD OR

Z-fold unit for FS-540/SD ZU-609

LEGEND

Option

respective option

Mandatory option

This option can only be installed with the above it

FINISHING FUNCTIONALITIES



































stapling

stapling

punching

punching

Duplex

Combined mixplex/ mixmedia

Half-fold

insertion

Tri-fold

Booklet

Offset sorting

printing

Stapling

DESCRIPTION

SC-509 Security kit

EM-908 Replacement SSD

KH-102 Keyboard holder

| ENHANCED FEATURES | |
|----------------------------------|---|
| LK-106 Barcode fonts | Supports native barcode printing |
| LK-107 Unicode fonts | Supports native Unicode printing |
| LK-108 OCR A and B fonts | Supports native OCR A and B font printing |
| LK-110v2 Document converter pack | Generates various file formats incl. DOCX, XLSX and PDF/A |
| LK-111 ThinPrint® client | Print data compression for reduced network impact |
| LK-116 Antivirus | Bitdefender® antivirus provides real time scanning of all |
| | incoming and outgoing data |
| | |
| CONNECTIVITY | |
| FK-514 Fax board | Super G3 fax, digital fax functionality |
| UK-221 Wireless LAN | Wireless LAN and wireless LAN Access Point Mode |
| EK-608 USB I/F kit | USB keyboard connection |
| EK-609 USB I/F kit | USB keyboard connection; Bluetooth |
| ID card reader | Various ID card technologies |
| MK-735 Mount kit | Installation kit for ID card reader |
| | |
| OTHERS | |
| WT-506 Working table | Authentication device placement |
| KP-102 10-Key pad | For use instead of touchscreen |

Copy guard function

To place USB keyboard

1 TB SSD to increase storage space

| IM-103 Intelligent media sensor | Detects paper type and weight automatically (Standard) |
|---------------------------------|---|
| PC-116 1x Universal tray | 500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m 2 |
| PC-216 2x Universal tray | 2x 500 sheets, 5.5" x 8.5" – 11" x 17" / 52–256 g/m ² |
| PC-416 Large capacity tray | 2,500 sheets, 8.5" x 11" / 52–256 g/m² |
| PC-417 Large capacity tray | 1,500 + 1,000 sheets, 5.5" x 8.5" or 8.5" x 11" / 52–256 g/m ² |
| LU-302 Large capacity tray | 3,000 sheets, 8.5" x 11" / 52–256 g/m ² |
| LU-207 Large capacity tray | 2,500 sheets, 8.5" x 11" – 12" x 18" / 52–256 g/m ² |
| MK-730 Banner tray | Multipage banner feeding |

| MEDIA OUTPUT | |
|------------------------------------|---|
| OT-513 Output tray | Output tray used instead of finisher |
| FS-539 Staple finisher | 50-sheet stapling; 3,200 sheets max. output |
| FS-539SD Booklet finisher | 50-sheet stapling; 20 sheets booklet finisher; |
| | 2,200 sheets max. output |
| PK-524 Punch kit for FS-539/SD | 2/3-hole punching; auto switching |
| FS-540 Staple finisher | 100-sheet stapling; 3,200 sheets max. output |
| FS-540SD Booklet finisher | 100-sheet stapling; 20 sheets booklet finisher; |
| | 2,700 sheets max. output |
| PK-526 Punch kit for FS-540/SD | 2/3-hole punching; auto switching |
| RU-513 Relay unit | For FS-539/SD or FS-540/SD installation |
| JS-602 Job separator for FS-540/SD | Separation of fax output; etc. |
| PI-507 Post inserter for FS-540/SD | Cover insertion; post finishing |
| ZU-609 Z-fold unit for FS-540/SD | Z-fold for A3 prints |
| FS-P04 Off-line stapler | 20-sheet off-line stapling |

TECHNICAL SPECIFICATIONS

| SYSTEM SPECIFICATIONS | |
|-----------------------------|---|
| System speed 8.5" x11" | Up to 65 ppm |
| System speed 11" x 17" | Up to 32 ppm |
| Autoduplex speed 8.5" x11" | Up to 65 ppm |
| 1st page out time 8.5" x11" | 2.8 sec. |
| Warm-up time | Approx. 15 sec. 1 |
| Imaging technology | Laser |
| Toner technology | Simitri® HD polymerized toner |
| Panel size/resolution | 10.1" / 1024 x 600 |
| System memory | 8,192 MB (standard/max) |
| System hard drive | 256 GB SSD (standard) / 1 TB SSD (optional) |
| Interface | 10/100/1,000-Base-T Ethernet; USB 2.0; |
| | Wi-Fi 802.11 b/g/n/ac (optional) |
| Network protocols | TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP(S) |
| Automatic document feeder | Up to 300 originals / 5.5" x 8.5" – 11" x 17" / |
| | 35–210 g/m² / Dual scan ADF |
| ADF double feed detection | Standard |
| Printable paper size | 3.5" x 5.5" – 12" x 18" / customized paper sizes / |
| | banner paper max. 47.2" x 11.7" |
| Printable paper weight | 52-300 g/m ² |
| Paper input capacity | 1,150 sheets / 6,650 sheets (standard/max) |
| Paper tray input (standard) | 1 x 500 /3.5" x 5.5" – 11" x 17" / custom sizes / 52–256 g/m ² |
| | 1 x 500 / 5.5" x 8.5" – 12" x 18" / custom sizes / 52–256 g/m 2 |
| Paper tray input (optional) | 1 x 500 / 5.5" x 8.5" – 11" x 17" / 52–256 g/m ² |
| | 2 x 500 / 5.5" x 8.5" – 11" x 17"/ 52–256 g/m ² |

1 x 2,500 / 8.5" x 11" /52-256 g/m²

 $52-256 \, g/m^2$

1 x 1,500 + 1 x 1,000 sheets / 5.5" x 8.5" or 8.5" x 11"/

| 0.0.20.200 | |
|--------------------------------|--|
| Large capacity tray (optional) | 1 x 3,000 / 8.5" x 11" / 52-256 g/m ² |
| | 1 x 2,500/ 8.5" x 11" – 12" x 18" / custom sizes / |
| | 52-256 g/m ² |
| Manual bypass | 150 sheets / 3.5" x 5.5" – 12" x 18" / custom sizes / |
| | banner / 60–300 g/m ² |
| Finishing modes (optional) | Offset; Group; Sort; Staple; Staple (offline); Punch; Half-fold; |
| | Letter-fold; Booklet; Post insertion; Z-fold |
| Automatic duplexing | 4.1" x 5.5" – 12" x 18" / 52–256 g/m ² |
| Output capacity | Up to 250 sheets / up to 3,300 sheets (standard/max) |
| Stapling | Max. 100 sheets or 98 sheets + 2 cover sheets (up to 300 g/m^2) |
| Stapling output capacity | Max. 200 sets |
| Tri-fold | Max. 3 sheets |
| Tri-fold capacity | Max. 50 sets; unlimited (without tray) |
| Booklet | Max. 20 sheets or 19 sheets + 1 cover sheet (up to 300 g/m^2) |
| Booklet output capacity | Max. 35 booklets; unlimited (without tray) |
| Duty cycle (monthly) | Rec. 53,000 pages; Max. ² 200,000 pages |
| Toner lifetime | Black up to 24,000 pages |
| Imaging unit lifetime | Black up to 240,000/1,000,000 pages (drum/developer) |
| Power consumption | 110-120 V / 60 Hz, Less than 1.6 kW |
| System dimension (W x D x H) | 24.2" x 27.1" x 37.8" (without options) |
| System weight | Approx. 220 lb (without options) |

SYSTEM SPECIFICATIONS

PRINTER SPECIFICATIONS

| Print resolution | 1,800 (equivalent) x 600 dpi; 1200 x 1200 dpi |
|---------------------------|--|
| Page description language | PostScript 3 (CPSI 3016); PCL 6 (XL3.0); PCL 5c; XPS |
| Operating systems | Windows 10 (32/64); Windows 11; Windows Server 2012; |
| | Windows Server 2012 R2; Windows Server 2016; |
| | Windows Server 2019; Windows Server 2022; |
| | macOS 10.14 or later; Unix; Linux; Citrix |
| Printer fonts | 80 PCL Latin; 137 PostScript 3 Emulation Latin |
| Mobile printing | Konica Minolta Print Service (Android); |
| | Konica Minolta Mobile Print (iOS/Android); |
| | AirPrint (iOS; Mopria (Android) |
| | optional: Wi-Fi Direct |
| | |

SCANNER SPECIFICATIONS

| Scan speed | Up to 140 ipm in simplex (mono) |
|-------------------|---|
| | Up to 280 ipm in duplex (mono) |
| Scan resolution | Up to 600 x 600 dpi |
| Scan modes | Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home); |
| | Scan-to-FTP; Scan-to-Box; Scan-to-USB; Scan-to-WebDAV; |
| | Scan-to-DPWS; Scan-to-URL; TWAIN scan |
| File formats | JPEG; TIFF; PDF; Compact PDF; Encrypted PDF; XPS; PPTX |
| | optional: Searchable PDF; PDF/A 1a and 1b; |
| | Searchable DOCX/PPTX/XLSX |
| Scan destinations | 2,000 destinations + 100 groups; LDAP support |
| | |

COPIER SPECIFICATIONS

| Copy resolution | 600 x 600 dpi |
|-----------------|-------------------------------------|
| Gradation | 256 gradations |
| Multicopy | 1–9,999 |
| Original format | Max. 11" x 17" |
| Magnification | 25–400% in 0.1% steps: Auto-zooming |

FAX SPECIFCIATION

| Fax standard | Super G3 (optional) |
|------------------|----------------------------|
| Fax transmission | Analog; i-Fax; Color i-Fax |
| Fax resolution | Up to 600 x 600 dpi |
| Fax compression | MH; MR; MMR; JBIG |
| Fax modem | Up to 33.6 Kbps |
| Fax destinations | 2,000 single + 100 groups |
| | |

USER BOX SPECIFICATIONS

| Storable documents | Up to 3,000 documents or 10,000 pages |
|------------------------------|---|
| Type of user boxes | Public; Personal (with password or authentication); |
| | Group (with authentication) |
| Type of system boxes | Secure print; Encrypted PDF print; Fax receipt; Fax polling |
| SYSTEM FEATURES | |
| Security | ISO 15408 HCD-PP Common Criteria (in evalutation); |
| | IP filtering and port blocking; SSL3 and TLS1.0/1.1/1.2 network |
| | communication; IPsec support; IEEE 802.1x support; |
| | User authentication; Authentication log; Secure print; Kerberos; |
| | Overwrite all data function; SSD Self-Encryption (AES 256)/ |
| | Storage lock password; Confidential fax; |
| | Print user data encryption |
| Security function (optional) | Antivirus realtime scanning (Bitdefender®); |
| | Copy protection (Copy Guard, Password Copy) |
| Accounting | Up to 1,000 user accounts; Active Directory support (user name + |
| | password + e-mail + smb folder); User function access definition; |
| | Authentication by mobile device (Android) |
| | ID card authentication (ID card reader); |
| | Authentication by mobile device (iOS) |
| Software | Net Care Device Manager; Data Administrator; Web Connection; |
| | Log Management Utility |
| | |

- All specifications refer to 8.5" x 11" paper of 80 g/m² weight.
- The support and availability of the listed specifications and functionalities varies depending on operating systems, applications and network protocols as well as network and system configurations.
- The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a
 particular page size (5% coverage of 8.5" x 11"). The actual life of each consumable will vary depending on use and
 other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient
 temperature and humidity.
- Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

























For complete information on Konica Minolta products and solutions, please visit: **CountOnKonicaMinolta.com**

© 2024 KONICA MINOLTA BUSINESS SOLUTIONS U.S.A., INC. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo and bizhub are registered trademarks or trademarks of KONICA MINOLTA, INC. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design & specifications are subject to change without notice.



Document Solutions

151 Sumner Avenue, Kenilworth, New Jersey 07033

NY | NJ | PA

NJ: 908.653.0600 NY: 212.468.5200

service@dsbls.com www.dsbls.com

¹ Warm-up time may vary depending on the operating environment and usage

 $^{^{2}}$ If the maximum volume is reached within a period of one year, then a maintenance cycle must be performed